



STONE PRIMER

PRODUCT DESCRIPTION

Santec Stone Primer Coat is a water base film forming cum impregnator for protection of polished or rough marble, granite and natural stone from mortar stain as well as water marks. Compatible on a humid or damp surface, therefore saving time during application process.

USES

- Use as a protection against back mortar stain which will appear and seen after final polishing of marble and grout
- Simple application
- Have a good bond with cement as well adhesive
- Very good for soft marble and high porous granite

FEATURES & BENEFITS

- Prevent good resistance against mortar stain
- Easy to apply
- Good bond with cement mortar
- Penetrating cum film forming
- Natural look remain intact

SUITABLE SURFACE

- Marble
- Granite
- Natural stone

SURFACE PREPARATION

Mixing Instruction

Ready to use

Application Process

Take a Santec Stone Primer in a clean container or spray bottle. Apply Santec Stone Primer on surface with brush or wiper or roller. Let the first coat dry and then apply the second coat in the perpendicular direction of the first coat.

Application Condition

- Residual moisture content of the stone substrate should not exceed 5%.
- No rising moisture & potential osmosis problems.
- Substrate temperature should be at least 3°C above dew point but not above 50°C.
- Recommended ambient temperature for application is between 10°C - 40°C.
- Relative Air Humidity (RH) to not exceed beyond 80%.

CLEANING

Required Residual traces of the product can be removed from tools with Santec Epoxy Remover before the product has hardened.

TECHNICAL DATA

Base	Acrylic Polymer
Aspect	Liquid
Colour	Milky White
pH	7 (5% in water)

CONSUMPTION

Any suitable surface	1 L - 5 to 6 sq.mt.
-----------------------------	---------------------

The data given is for guideline only. The physical values are subject to normal manufacturing tolerances, colour and testing variances. The coverage & consumption figures are theoretical and do not allow for any additional material required due to surface porosity, surface profile, variations in level or wastage etc.

PACKAGING

- 1 KG
- 5 KG
- 10 KG
- 20 KG

STORAGE & SHELF LIFE

Keep in a cool and well ventilated area.
For best result, use within 7 days from opening to avoid possible spoilage.
For product expiry information, please refer to the product packing.

ANNOTATION

- Do not apply wet to wet coats.
- Always remove back net before application.
- Surface should be dry before application.
- Apply in a shade area.
- Always use good quality brush, sponge, scrubber or white cotton cloth while application to avoid damaging the surface due to the decolorization.
- While using any tools like spray pumps, low hand pressure pumps, water jets, mixer machines, grinding machines in application, clean the inner and outer surface of the tool to avoid any kind of damage to the surface and material to be used.

HEALTH & SAFETY

Precautions

- During application wear protective clothing, gloves and eye goggles during application. Avoid products to contact eyes and skin.
- Keep out of reach of children.
- Not for internal consumption
- Apply between temp. 5°C to 35°C.
- Use only in well ventilated areas.
- Wash hands thoroughly after applying.

Accident

- Use water spray

Spillage

- Take up mechanically or with absorbent material

First Aid

- If swallowed, contact a physician.
- If in skin contact wash skin with water and remove contaminated clothing.
- If you come in contact with the eye, hold open, flood with water for at least 10 min and contact a physician.

NOTES

The information above is believed to be accurate and represents the best information currently available to Santec Chemical Private Limited . However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall the Santec Chemistry Private Limited be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, however arising, even if the company has been advised of the possibility of such damages. Users must always refer to the most recent issue of the local product datasheet.

Always test on a small area First and allow a 24 hour cure time to determine the ease of application and desire time.

COMPANY DETAILS

Corporate Office : SANTEC CHEMICAL
PRIVATE LIMITED, Malappuram, Kerala, India.

Call : +91 7247 555 666

E-mail : info@santecchemicals.com

Website : www.santecchemicals.com

For feedback or complaints, write to Marketing
Manager Services on the above mentioned
address.